

# *PRICE AND GESS*

ATTORNEYS AT LAW

2100 S.E. MAIN STREET, SUITE 250

IRVINE, CALIFORNIA 92614-6238

JOSEPH W. PRICE  
ALBIN H. GESS  
MICHAEL J. MOFFATT  
GORDON E. GRAY III  
BRADLEY D. BLANCHE  
J. RONALD RICHEBOURG

OF COUNSEL  
JAMES F. KIRK

A PROFESSIONAL CORPORATION  
TELEPHONE: (949) 261-8433  
FACSIMILE: (949) 261-9072  
FACSIMILE: (949) 261-1726

e-mail: [pg@pgpatentlaw.com](mailto:pg@pgpatentlaw.com)

## **SPECIFICATION, CLAIMS AND ABSTRACT**

Inventor(s): **David A. Richard**

Title: **A VARIABLE TRANSMITTANCE BIREFRINGENT  
DEVICE**

Attorney's  
Docket No.: **VTE1-BO14**

**EXPRESS MAIL LABEL NO. EL852658850US**  
**DATE OF DEPOSIT: March 29, 2001**

PATENT APPLICATION

**A VARIABLE TRANSMITTANCE BIREFRINGENT DEVICE**

David A. Richard

5

## A VARIABLE TRANSMITTANCE BIREFRINGENT DEVICE

### BACKGROUND OF THE INVENTION

#### FIELD OF THE INVENTION

10           The present invention relates generally to a variable transmittance birefringent device, and specifically to a variable reflectance vehicle mirror which electrically controls reflectivity thereof by use of a birefringent medium.

#### DESCRIPTION OF RELATED ART

15           A familiar hazard for the driver of a vehicle is that of being 'blinded' by the glare of light beams from the headlights of a following vehicle, such beams being reflected by the rearview mirror of the driver's vehicle. In order to avoid this glare, prismatic rearview mirrors are used in the interior of a vehicle which can be switched from a high to a low reflecting state by use of a manual lever located on the mirror. Under ordinary  
20           driving conditions, the high reflecting state of the mirror is used to provide optimal rear visibility. At night, the interior mirror is often switched to its low reflecting state to prevent the driver from being blinded by the headlights of following vehicles. The low reflectivity state of the mirror typically exhibits non-spectral selectivity, where the background of an image viewed in the low reflectivity state of the prismatic mirror would  
25           be color neutral.

          With the advent of electro-optic technology, it has become possible to achieve continuous variability in reflectivity in rearview mirrors for motor vehicles. This variability has been achieved, for example, through the use of electrochromic devices, wherein the intensity of light is modulated by passing the light through an electrochromic  
30           (EC) cell. Electrochromism describes materials which change color when their composition is changed by use of an electrochemical cell, which enables the materials to be reversibly colored or bleached. In such devices, the EC cell includes an electrochromic medium disposed between two conductive electrodes which undergoes Electrochromism when potential differences are applied across the two electrodes.

5 Antiglare mirrors for use in vehicles using a solution-phase or gel-type EC cell and thin-film type EC cell have been conventionally proposed. The solution-phase or gel-type EC cell, which is formed of a liquid or gel material such as biogen compound sealed between glass substrates, uses coloring due to oxidation/reduction of the biogen compound when a voltage is applied to the glass substrates. The thin-film type EC cell, 10 which is formed of a transient metal oxide such as  $WO_3$  vapor-deposited on the glass substrates, uses coloring due to injection of hydrogen and metal ions into and emission thereof when a voltage is applied to the glass substrates. Therefore, whether the anti-glare mirror uses the solution phase type EC, the gel-type EC or the thin-film type EC cell, as the applied voltage becomes high, its mirror reflectivity decreases due to the 15 coloring of the EC cell, and when the applied voltage is removed, the reflectivity is restored to its initial value.

Mirrors employing EC cells have several drawbacks. In order to provide a rapid change in intensity and uniformity in the coloring of the EC cell, very large electrical contacts extending substantially along the entire length of the top and bottom surfaces of 20 the mirror are required. Thus, these mirrors require bevels or rims to cover and insulate these electrical contacts, which increase the size, cost, and complexity of the mirrors. Furthermore, use of a gel-type or solution-phase EC cell is undesirable due to the likelihood of the electrochromic medium leaking out of mirror should the mirror become damaged. The leakage of the electrochromic medium can not only be dangerous to 25 passengers in the vehicle who are exposed to the electrochromic medium, but leakage of the electrochromic medium can further render the mirror non-functional. The constituency of the EC cell is damaging to the interior dashboard and exterior finish of the vehicles on which they are mounted should the mirror become cracked or the cell ruptured by impact or collision causing the contents to leak out. Electrochromic devices 30 may also exhibit deleterious performance when exposed to ultraviolet radiation over prolonged periods of time, which may be linked to a variety of sources including a potential propensity for photochromism to occur.

Vehicles are typically equipped with an interior rearview mirror as well as exterior mirrors outside of the driver and passenger doors. In order to prevent the driver 35 from being subjected to a glare from rearward light reflected from any of these mirrors,

5 each of the mirrors must have a controlled reflectivity. In current systems having mirrors  
possessing EC cells, it is known to utilize a singular drive circuit to control all of the  
mirrors. This drive circuit is typically housed with the interior mirror, requiring a  
dedicated wire harness and specific input voltage to control and activate the EC cells on  
the exterior mirrors of the vehicle. All of the EC cells within the system are uniformly  
10 activated by the drive circuit, even when the dazzle or glare is only coming from one of  
the mirrors. This uniform activation of all of the mirrors unnecessarily reduces the image  
quality of the other mirrors where no dazzle or vision impairing is present.

Mirrors are also known which make use of the properties of nematic liquid  
crystals which are normally transparent to light but which when subjected to a sufficient  
15 electrical voltage beyond a certain threshold, present a state of turbulence so that the light  
is attenuated to an increasing degree as the applied electric field is increased. Upon  
suppressing the applied electric field, the liquid crystal returns to the transparent state.  
Using such mirrors, therefore, it is possible to obtain selectively a high or a low reflecting  
power, according to whether the electrical voltage acting on the liquid crystal is lower or  
20 greater than said threshold. The chief drawback of conventional liquid crystal mirrors is  
that when the mirrors work in conditions of weak reflecting power the images of objects  
viewed by reflection in the mirror are considerably dimmed. In these types of liquid  
crystal mirrors, either Chromium or Rhodium plated or deposited surfaces are used as the  
reflective medium. These mediums offer only a 50 to 55% reflectivity in the visible  
25 wavelengths, thus reducing the image brightness even in the non-activated state.

Some examples of these prior art liquid crystal mirrors are described in U.S.  
Patent No. 3,862,798 issued to Hopkins and U.S. Patent No. 4,200,361 issued to  
Malvano. These patents describe nematic liquid crystal devices having a liquid crystal  
film sandwiched between front and rear transparent electrode surfaces, where the nematic  
30 liquid crystal mirrors of these types are typically only capable of transmitting 50% of  
available light. With the standard 3% loss of transmission between the air to substrate  
interface and the fact that the light, in reflection, must travel back through the device,  
there is an additional 6% loss of transmission, not with standing the liquid crystal film  
absorption. This rendered mirrors employing typical liquid crystal cells capable of, at  
35 best, 44% transmission of the incident light. This phenomenon directly resulted from the

5 use of uncompensated-for polarized light in the reflective devise. Aside from typically exhibiting poor reflectivity, mirrors employing conventional liquid crystal materials have also generally suffered from having an insufficient viewing angle, low contrast ratios, and variable response times with temperature fluctuation.

## 10 SUMMARY OF THE INVENTION

The foregoing shortcomings and disadvantages of the prior art are alleviated by the present invention that provides a variable reflectance mirror employing a super-twisted nematic (STN) liquid crystal cell to control reflectivity. The STN liquid crystal cell includes a pair of transparent electrically insulating plates serving as front and rear  
15 plates for the liquid crystal cell, where these plates may comprise glass or an optical grade, stable synthetic plastic. The facing surfaces of each of these plates are coated with a transparent metal oxide film, which acts as an electrode. A layer of STN liquid crystal material is formed in the area between the electrodes, where a polymer alignment layer is formed over the conductive layers and in contact with the STN liquid crystal material.  
20 The alignment layer is treated in a way so as to orient the STN liquid crystal material to possess a twist angle between approximately  $180^\circ$  and approximately  $270^\circ$ . A pair of crossed polarizers are respectively positioned on the outer surfaces of the front and rear plates. A layer of reflective material is further formed adjacent to the outer surface of the polarizer adjacent to the rear plate, where the reflective layer is affixed to the rear  
25 polarizer by a bonding layer. The variable reflectance mirror includes a front transparent cover element which is affixed to the front polarizer by a bonding layer and a rear transparent cover element positioned adjacent to the reflective layer, wherein the front and rear transparent cover elements form the outer surfaces of the mirror.

The conductive layers are connected to a voltage source to apply an electrical bias  
30 to the STN liquid crystal layer, where the transmittivity of the STN liquid crystal layer to light can be varied by varying the electrical bias applied across the conductive layers. When little or no voltage is applied across the conductive layers, the liquid crystal layer is essentially transparent to light. As a voltage is applied across the transparent electrodes, the twist angle of the STN liquid crystal layer changes to make the layer more opaque

5 and to scatter light. The degree of opaqueness achieved in the STN liquid crystal layer is proportional to the amount of voltage applied across the transparent electrodes. The degree of reflection provided by the variable reflectance mirror is adjusted by adjusting the electrical bias applied across the STN liquid crystal layer.

10 A control circuit is connected to the STN liquid crystal cell to control the electrical bias applied across the STN liquid crystal layer. A rear light detecting sensor and an ambient light detecting sensor are further connected to the control circuit for determining the intensity of the light impinging on the variable reflectance mirror from the rear of the vehicle. The control circuit adjusts the reflectivity of the variable reflectance mirror based upon the intensity of the light measurements made by the A rear  
15 light detecting sensor and an ambient light detecting sensor.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The features of the present invention, which are believed to be novel, are set forth with particularity in the appended claims. The present invention, both as to its organization and manner of operation, together with further advantages, may best be understood by  
20 reference to the following description, taken in connection with the accompanying drawings in which the reference numerals designate like parts throughout the figures thereof and wherein:

FIG. 1 is a perspective view of a vehicle showing the arrangement of rearview  
25 mirrors on the vehicle;

FIG. 2 is a cross-sectional view of a preferred embodiment of the variable reflectance mirror of the present invention;

FIG. 3 is a partial cutaway perspective view of a preferred embodiment of the variable reflectance mirror of the present invention;

30 FIG. 4 is a schematic view of the variable reflectance mirror of the present invention and its associated control circuitry; and

FIG. 5 is a circuit diagram of a preferred embodiment of the control circuit for the variable reflectance mirror of the present invention.

## 5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following description is provided to enable any person skilled in the art to make and use the invention and sets forth the best modes contemplated by the inventors of carrying out their invention. Various modifications, however, will remain readily apparent to those skilled in the art, since the general principles of the present invention have been defined herein specifically to provide a variable reflectance vehicle mirror.

The present invention is directed toward a variable transmittance birefringent device and, more particularly, to an independently-driven variable reflectance vehicle mirror which utilizes a birefringent medium to a continuous range of reflectivity. As illustrated in FIG. 1, the variable reflectance mirror of the present invention may be utilized as the internal rearview mirror 10 or the external mirrors 12 and 14 respectively positioned outside the driver and passenger doors of a vehicle. While the discussion of the present invention will focus upon the variable reflectance mirror being utilized in a vehicle, it is not the intention of the inventor of the present invention to limit its use to within vehicles and the variable reflectance mirror of the present invention may be utilized for other types of mirrors where attenuation of the reflectivity of the mirror is desired.

Referring now to FIG. 2, a cross-sectional view of a variable reflectance mirror 200 formed in accordance with a preferred embodiment of the present invention is illustrated. The mirror employs a super-twisted nematic liquid crystal cell 202 to control the transmittance of light there through and, in turn, the reflectivity of the mirror. The liquid crystal cell 202 includes a pair of transparent electrically insulating plates 204 and 206 respectively serving as front and rear plates for the liquid crystal cell 202. Plates 204 and 206 may comprise glass, an optical grade, stable synthetic plastic, or other suitable optically transmissive medium. A pair of transparent electrodes 208 and 210 are respectively formed on the facing surfaces of plates 208 and 210, where transparent electrodes 208 and 210 are preferably a transparent metal oxide film, such as indium-tin-oxide (ITO) or other similar metal oxide conductive layers. Transparent electrodes 208 and 210 may be formed as a solid layer, or may alternatively be patterned, such as to form rows and columns as in a passive matrix display or to form individual pixels as in an active matrix display.

A layer of super-twisted nematic liquid crystal material 212 is formed in an area between the transparent electrodes 208 and 210. The transparent electrodes 208 and 210 are



5 connected to a voltage source for applying an electrical bias across the liquid crystal layer 212. The transmittivity of the liquid crystal layer 212 to light can be varied by varying the electrical bias applied across the transparent electrodes 208 and 210. When little or no voltage is applied across the transparent electrodes 208 and 210, the liquid crystal layer 212 is essentially transparent to light. As a voltage is applied across the transparent electrodes 10 208 and 210, the liquid crystal layer 212 becomes more opaque and scatters light. The degree of opacity achieved in the liquid crystal layer 212 is proportional to the amount of voltage applied across the transparent electrodes 208 and 210. Light entering the variable reflectance mirror 200 passes through the liquid crystal layer 212 until it reaches a reflecting layer 214 which reflects the light back through the liquid crystal layer 212 toward a viewer. 15 Thus, the degree of reflection provided by the variable reflectance mirror 200 is adjusted by varying the electrical bias applied across the liquid crystal layer 212.

The liquid crystal cell 202 includes polymer alignment layers 216 and 218 formed over the transparent electrodes 208 and 210 and in contact with the liquid crystal layer 212. The alignment layers 216 and 218 are treated in a way so as to orient the liquid crystal 20 molecules in the liquid crystal layer 212 to a desired orientation. The alignment or orientation of the liquid crystal molecules occurs along a preferred direction, e.g. introduced by rubbing of an orientation layer, and at a certain angle with respect to the plane of the inside of the two transparent plates 204 and 206 which support the transparent electrodes 208 and 210. This latter angle is referred to as the tilt angle. The alignment layers 216 and 25 218 undergo a rubbing process which leaves a series of parallel microscopic grooves in the alignment layers 216 and 218. These grooves help align the liquid crystal molecules in a preferred direction, with their longitudinal axes parallel to the grooves. This anchors the liquid crystal molecules along the alignment layers 216 and 218 and helps to force the molecules between the alignment layers to twist. After rubbing both alignment layers 216 30 and 218, they are rotated by a certain angle around the axis perpendicular to the main plane in order to establish the so called twist angle of the liquid crystal molecules between the alignment layers 216 and 218. The alignment layers 216 and 218 may be applied in any number of ways, including but not limited to solution casting, e.g. spin coating, roller coating, dipping, spraying, printing and/or doctor blading, of the appropriate polymer or its

5 precursor. After removal of the solvents and/or curing of the polymer layers, the alignment layers 216 and 218 are usually rubbed or buffed in one direction with cloths.

In order to form the liquid crystal cell 202, the transparent plates 204 and 206 are adhered together around their periphery using a conventional adhesive for forming liquid crystal displays, e.g. using organic adhesives. In order to preserve a constant thickness of  
10 the space or gap between the transparent plates 204 and 206, suitable spacers 215 may be positioned in the frame adhesive and/or over the entire opposing surfaces of the transparent plates 204 and 206, as shown in FIG. 3. The gap between the transparent plates 204 and 206 is filled with a super-twisted nematic (STN) liquid crystal material and finally sealed using a similar organic adhesive as the frame adhesive. It is also possible to include suspended  
15 spacing spheres 213 in the STN liquid crystal material to assist in maintaining a constant thickness in the gap between the transparent plates 204 and 206. At this stage, a pair of crossed polarizers 220 and 222 are attached to the outer surfaces of the transparent plates 204 and 206, where the operation of the crossed polarizers in conjunction with the STN liquid crystal cell 202 will be described in greater detail hereinbelow. Electrical connections  
20 are made to the transparent electrodes 208 and 210 in a manner consistent with known liquid crystal display designs. The layer of reflective material 214 is further formed on the outer (posterior) surface of the polarizer 222 adjacent to the rear plate 206. The reflective layer 214 is preferably an enhanced aluminum material or other similar highly reflective material. A layer of bonding material 223 affixes the reflective layer 214 to the rear polarizer 222.  
25 The bonding layer 223 may comprise an optically clear aliphatic isocyanate or a cyanoacrylate material or other similar transparent bonding material.

Referring now to FIG. 3, a partial cutaway perspective view of the variable reflectance mirror 200 incorporating the STN liquid crystal cell 202 is shown. The variable reflectance mirror further includes anterior outer panel 224 and posterior outer panel 226,  
30 where the anterior side of the variable reflectance mirror 200 is that facing a viewer 225. The outer panels 224 and 226 preferably comprise glass or a polymer having optical characteristics similar to glass, where the polymer may include but is not limited to acrylic (PMMA), polycarbonate, cyclic olefins, styrene, acrylic/styrene, CR-39® (PPG Industries), acetate, polyvinyl buterate, or polyurethane. A layer of bonding material 225 similar to  
35 bonding layer 223 affixes the anterior outer panel 224 to the front polarizer 220. The

reflective layer 214 is preferably positioned on the anterior side of the posterior outer panel 226. The character of the outer panels 224 and 226 can be further enhanced through the application of light path and reflectivity enhancing organic or inorganic coatings. Such coatings may be applied through a variety of methods, such as but not limited to dipping, spraying, or vacuum deposition. Such coatings may be utilized to enhance the weatherability of the assembly through the application of anti-abrasion and anti-reflective first and second surface coatings. For instance, in order to provide the outer panels 224 and 226 with a sufficient degree of scratch resistivity, the polymer outer panels 224 and 226 may be coated on all surfaces with an abrasion resistant "tie bond" coating that has a base of an organo-silicone (methylpolysiloxane) polymer with a thickness of approximately 2 to 10 microns. The polymer outer panels 224 and 226 may be coated with additional hydrophilic layers of Zirconia and Silicone Dioxide, a typical description of the coating formula would be described as a tiebond "hardcoat" of 2-3 uM thickness, 2616 angstrom of SiO<sub>2</sub>, 246 angstrom of ZrO<sub>2</sub>, 174 angstrom of SiO<sub>2</sub>, 765 angstrom of ZrO<sub>2</sub>, 907 angstrom of SiO<sub>2</sub>. Alternately, an additional layer of hydrophobic acting perfluoroalkylsilane may be added to either or both of the external surfaces of the polymer outer panels 224 and 226 to form a strongly adherent fluorised siloxane coating. The optimal coating thickness for the perfluoroalkylsilane is approximately 5-20 nm.

Each of the polymer outer panels 224 and 226 may further be UV (ultra-violet) stabilized with a UV inhibitors in order to prevent color degradation over time. Typical UV inhibitors which may be utilized are as follows: Cyagard 1164L, Cyagard 3638, Cyagard UV 531, Cyagard UV 5411, Cyagard UV 9, Cyasorb 1084, Cyasorb 1164, Cyasorb 284, Cyasorb UV 1988, Cyasorb UV 2098, Cyasorb UV 2126, Cyasorb UV 24, Cyasorb UV 2908, Eastman Inhibitor RMB, Givisorb UV-1, Givisorb UV-2, Givisorb UV-13, Givisorb UV-14, Givisorb UV-15, Givisorb UV-16, Mark 1535, Mark 446, Maxgard 200, Maxgard 800, Norbloc 6000, Norbloc 7966, Quercetin, Sanduvor 3206, Sanduvor EPU, Sanduvor VSU, Seesorb 201, Syntase 1200, THPE BZT, Tinuvin 99, Tinuvin 109, Tinuvin 1130, Tinuvin 120, Tinuvin 1545, Tinuvin 1577FF, Tinuvin 320, Tinuvin 326, Tinuvin 327, Tinuvin 328, Tinuvin 384, Tinuvin 400, Tinuvin 571, Tinuvin 840, Tinuvin 900, Tinuvin 928, Tinuvin P, Uvinul 3035, Uvinul 3039, Uvinul 3048, Uvinul 400, Uvinul D 49, Uvinul D 50, Uvinul P 25, Uvinul T-150.

5           The liquid crystal cell 202 of the present invention contains a layer of super-twisted nematic (STN) liquid crystal material 212. Unlike mirrors employing conventional nematic liquid crystal materials which only provide a twist angle of  $90^\circ$  between electrodes, the STN liquid crystal material 212 of the present invention undergoes a greater than  $90^\circ$  twist between the transparent electrodes 208 and 210. The transmission axes of the polarizers 222 and 224 are preferably positioned in a direction at an optimized, non-parallel angle with respect to the orientation of the liquid crystal molecules at the surfaces of the liquid crystal layer 212. A significant attribute of this STN liquid crystal cell 202 used in the current invention is the ability of the STN liquid crystal molecules to twist between approximately  $180^\circ$  and approximately  $270^\circ$ , where the preferred twist angle of the STN liquid crystal molecules is  $210^\circ$  which provides a broad transition region enabling full grayscale attenuation. This added rotation of the STN liquid crystal molecules of the present invention over conventional TN cells provides steeper tilt angles of the transparent plates 204 and 206, gives the crystal a much steeper voltage-brightness response curve, and also widens the angle at which the variable reflectance mirror 200 can be viewed before losing contrast. With the sharper response of the present invention, it is possible to achieve higher contrast without requiring increased voltage ratios.

          The STN liquid crystal material 212 of the present invention is birefringent due to its anisotropic nature, where liquid crystals have two indices of refraction and demonstrate double refraction. When light enters a birefringent material, the light is broken up into the fast (called the ordinary ray) and slow (called the extraordinary ray) components. Because the two components travel at different velocities, the waves get out of phase. When the rays are recombined as they exit the birefringent material, the polarization state of the light has changed because of this phase difference. In the present invention, the STN liquid crystal cell 202 is placed between crossed polarizers 220 and 222 whose transmission axes are aligned at some angle between the fast and slow direction of the STN liquid crystal material 212. Because of the birefringent nature of the STN nematic liquid crystal material 212, the incoming linearly polarized light becomes elliptically polarized. When this light reaches the rear polarizer 222, there is now a component of light that can pass through. As light travels through the STN cell, its polarization rotates with the twist angle of the liquid crystal molecules. The magnitude of the phase difference is determined by the twist angle of the

5 STN liquid crystal material 212 between the crossed polarizers 220 and 222, where the amount of the phase shift determines the intensity of the light which passes through the STN liquid crystal cell 202 to the reflecting layer 214 and which is further reflected back through the STN liquid crystal cell 202.

10 The STN liquid crystal cell 202 is connected to a control circuit which controls the voltage applied across the STN cell. Depending on the strength of the electric field applied across the STN liquid crystal cell 202, the STN liquid crystal cell 202 can change the twist angle of the liquid crystal molecules and, in turn, the polarization of the light passing through the STN liquid crystal cell 202. Thus, the STN liquid crystal cell 202 can provide full grayscale attenuation of the light passing there through to control reflectivity of the variable reflectance mirror in a continuous range between approximately 28% and 94% of full reflectivity. Due to the standard 3% to 4% loss of transmission between the air to substrate interface and the fact that the light, in reflection, must travel back through the device, there is a minimal 6% to 8% loss of transmission resulting in a maximal reflectivity of 92% to 94% . The variable reflectance mirror 200 is capable of controlling reflectivity to a level below 28%; however, safety standards set the current minimal level of reflectivity at 28%. In the STN liquid crystal cell of the present invention, the cell thickness and the birefringence of the STN liquid crystal constituency are carefully chosen for the present invention to result in a high level of transparency during the rest state.

25 The performance of liquid crystal devices are measured by their contrast ratio. This is described as the luminance of the bright state divided by the luminance of the dark state. In the ideal liquid crystal cell the luminance of the bright state would be high (transparent) and the luminance of the dark state would be low (black) and this would be true for large percentages of the viewing angles. In the devices employing conventional TN liquid crystal cells, the luminance of the bright state is approximately constant for changing viewing angles while the dark state has a lot of light leakage off axis, resulting in the contrast ratio varying greatly as a function of the viewing angle. In the conventional TN liquid crystal devices, a very steep electro-optic transfer characteristic is required to be able to achieve a suitable contrast ratio for the device where the limit for the contrast ratio for such devices is 64:1. The STN liquid crystal material used in the present invention has much steeper electro-optic transfer characteristics with contrast ratios of up to 480:1.

5 In an alternative embodiment of the present invention, the variable reflectance mirror 200 of the present invention may be formed to be rimless or bezelless. After the various layers of the variable reflectance mirror 200 are formed together, the layers are then trimmed to form a mirror of a desired peripheral geometry. The layers are preferably trimmed using a water jet process which fuses the outer surfaces of the various layers  
10 together as it trims the mirror to provide a weather-resistance seal around the outer periphery of the trimmed mirror. The inventor of the present invention recognizes that it is also possible to utilize other similar methods of trimming the layers to produce the trimmed mirror of the present invention. With this rimless construction, the outer periphery of the mirror only requires two small openings to provide electrical contact with the transparent  
15 electrodes 208 and 210 in the STN liquid crystal cell 202. The rimless construction of this embodiment of the present invention provides a lightweight, compact and versatile variable reflectance mirror 200.

The variable reflectance mirror 200 includes a control circuit 300 for applying a voltage bias across the transparent electrodes 208 and 210 to control the reflectivity of the  
20 mirror 200, as shown in the schematic diagram of FIG. 4. An ambient light detecting sensor 302 detects the external light conditions surrounding the vehicle on which the variable reflectance mirror 200 is installed. The ambient light detecting sensor 302 is preferably disposed on a housing for the mirror and facing a direction other than the rear of the vehicle. A rear light detecting sensor 304 is further provided for detecting the lighting impinging on  
25 the variable reflectance mirror 200 from the rear of the vehicle. Based upon the output from the ambient light detecting sensor 302 and the rear light detecting sensor 304, the control circuit 300 determines the required amount of attenuation of reflectivity of the variable reflectance mirror 200 and generates a corresponding voltage bias across the transparent electrodes 208 and 210. The two light detecting sensors 302 and 304 possess independent,  
30 non-interactive, responses to the control circuit 300.

Referring now to FIG. 5, a detailed schematic of the control circuit 300 is illustrated. The control circuit 300 is preferably formed using a single CMOS stacked integrated circuit (IC) 301 which is packaged in a 16-pin dual in-line package (DIP), such as the CYT16181 IC chip manufactured by VTEC Technologies, Inc. This use of a CMOS stacked IC 301  
35 provides an extremely compact control device that can be easily attached to the rear of the

5 mirror 200. The ambient light detecting sensor 302 monitors the surrounding ambient light conditions and only allows the control circuit 300 to alter the reflectivity of the variable reflectance mirror 200 when the ambient light conditions are below a predefined threshold. When the ambient light conditions are greater than the predefined threshold, it is assumed that light impinging on the variable reflectance mirror 200 from the rear of the vehicle will  
10 not produce a glare effect to the driver of the vehicle and control of the variable reflectance mirror 200 is deactivated. The ambient light detecting sensor 302 includes a photosensor 306, a capacitor 308, and a resistor 310. The values of the capacitor 308 and the resistor 310 may be selected so as to set the independent value of the threshold for background ambient light to determine when to activate or deactivate the reflection dimming activity of the  
15 control circuit 300. The rear light detecting sensor 304 includes a photosensor 312, a capacitor 314, and a resistor 316. The values of the capacitor 314 and the resistor 316 may be selected to set a threshold value for when a sensed rear light is bright enough to cause to glare to the driver and to dim the reflectivity of the variable reflectance mirror 200 an appropriate amount. Based upon the intensity of the rear light sensed by the rear light  
20 detecting sensor 304, the control circuit 300 determines the amount of dimming required to compensate for the glare causing effect of the sensed rear light.

The control circuit 300 includes a voltage regulating circuit 318 which receives a voltage input (V+) from a voltage source on the vehicle and generates a fixed voltage source for the variable reflectance mirror 200. The voltage regulating circuit 318 includes a resistor  
25 334, capacitor 336, and zenor diode 338. The voltage regulating circuit 318 may receive a voltage input (V+) from approximately 6 volts dc to approximately 40 volts dc, which enables the variable reflectance mirror 200 to be utilized on a wide variety of vehicles having various voltage sources. For instance, automobiles typically possess a 12 volt dc source while trucks typically possess a 36 volt dc voltage source. The voltage regulating  
30 circuit 318 converts the received voltage input (V+) to a voltage source used to drive the variable reflectance mirror 200, wherein the generated driving voltage for the variable reflectance mirror is in the range of approximately 2.7 to 5.5 volts dc. This enables the variable reflectance mirror 200 of the present invention to be entirely retrofittable in almost any existing vehicle, where only a voltage source from an existing power harness needs to  
35 be connected to the voltage regulating circuit 318. Furthermore, since the output of the

5 voltage regulating circuit 318 may also be varied by varying the values its respective components, the control circuit 300 of the present invention is also capable of driving a plurality of different types of STN liquid crystal cells having various driving requirements.

The control circuit 300 sets the driving frequency of the STN liquid crystal cell 202 using a resistor 320/capacitor 322 pair. The driving frequency of the STN liquid crystal cell  
10 202 may be adjusted between values of approximately 10 Hz to approximately 3KHz by varying the value of the resistor 320. The stacked IC 301 also includes an oscillator circuit which sets the clock generation for the STN liquid crystal cell 200 by setting the values of resistor 324 and diode 326. The control circuit 300 is connected to the STN liquid crystal cell 200 through electrical leads 330 and 332 which are respectively connected to  
15 transparent electrodes 208 and 210. The control circuit 300 provides the necessary flexibility for the display operating frequency and operating voltage of user assigned specific display characteristics. Through this control, the present invention rejects the spot lighting projection of light energy impinging on the variable reflectance mirror 200 from the rear of the vehicle and independently monitors the background illumination around the  
20 mirror 200 for the purposes of attenuating the reflectivity of the mirror 200. The variable reflectance mirror 200 of the present invention maintains full attenuation of reflectivity and display characteristics in temperatures between approximately  $-10^{\circ}$  C and  $90^{\circ}$  C, which provides significantly improved display visibility over conventional liquid crystal mirrors.

As can be seen from the foregoing, a variable reflectance mirror formed in  
25 accordance with the present invention utilizes a STN liquid crystal cell to provide exceptional levels of reflectivity not achievable through the use of conventional TN liquid crystal materials. Further, the STN liquid crystal cell of the present invention provides a variable reflectance mirror having an improved viewing angle, higher contrast ratio, and an efficient response time within normal temperature fluctuations. Additionally, the STN  
30 liquid crystal cell of the present invention allows a rimless variable reflectance mirror to be produced by eliminating the need for large electrical contacts while achieving a quick and uniform response to changes in reflectivity throughout the mirror surface.

In each of the above embodiments, the different structures of the variable reflectance mirror are described separately in each of the embodiments. However, it is the full intention  
35 of the inventors of the present invention that the separate aspects of each embodiment



5 described herein may be combined with the other embodiments described herein. Those skilled in the art will appreciate that various adaptations and modifications of the just-described preferred embodiment can be configured without departing from the scope and spirit of the invention. Therefore, it is to be understood that, within the scope of the appended claims, the invention may be practiced other than as specifically described herein.

10

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
222